





SANICUBIC® 1 SC

SEWAGE LIFTING UNITS



SEWAGE
WC, bathroom, kitchen and laundry

↑ 22 m



SANICUBIC® 1 SC

SEWAGE LIFTING UNITS

BENEFITS

- High performance: 1 single channel pump in three phases
- Custom dimensions, custom inlets and on-site-assembly possible (volume up to 20,000 litres available)
- Blockage-free operation by 80 mm solids handling
- Comfort control unit included in delivery


APPLICATIONS

- Drainage of sewage from apartment buildings or industrial enterprises etc.
- Above-ground installation in frost-free rooms below the backflow level

FEATURES

- Polyethylene container
- Pump housing with flanged outlet bend DN 100
- Lateral inlet with loose-type flange DN 150
- Additional connection 1 1/2" for manual diaphragm pump
- Star-delta-start for 7.5 kW unit
- Operation temperature max. 55°C
- Operating mode S3 - 25%
- Switching volume adjustable

PUMP GRAPH



REFERENCE	EAN	FACTORY CODE	SYSTEM	TANK (L)	SWITCHING VOLUME(L)	UVI	P1 (W)	P2 (W)	FREQUENCY (Hz)	INDM (A)	TR/MN	POWER CLASS	Q MAX (l/h)	H MAX (m)	WEIGHT (kg)	REMOTE CONTROL	POWER CLASS CONTROL	ALARM
SANICUBIC 1 SC3.0 T	3 308 815 079 035	CUBIC1SC3.0T	Single Channel	480	270	400	4,000	3,000	50/60	6.9	1,400	IP 57	120	10	210	ZPS1	IP 65	External, wired
SANICUBIC 1 SC4.0 T	3 308 815 079 042	CUBIC1SC4.0T					5,500	4,000		11.2			140	13	220			
SANICUBIC 1 SC5.5 T	3 308 815 079 059	CUBIC1SC5.5T					6,300	5,500		12.1			160	18	225			
SANICUBIC 1 SC7.5 T	3 308 815 079 066	CUBIC1SC7.5T					8,700	7,500		16.9			165	22	240			